

Visit www.prefEQ.com or Call Us @ 1-800-711-8698

PALLET STRETCH WRAPPERS

Basic Wrapper Types:



◀ Low Profile Turntable

Turntable is 3" - 4" above the floor, pallet is loaded with pallet jack using an optional ramp, or directly with a forklift truck. The unit can be set into a pit in the floor to provide floor level access to the turntable without the use of a ramp.



High Profile Turntable ▶

Turntable is raised 11" - 12" from the floor, pallet is loaded with a forklift truck or interfaced with a pallet conveyor line to feed pallets directly onto the wrapping machine turntable with an optional conveyor.



◀ Rotary Arm Machines

Pallets are placed directly on the floor. The arm rotates around the pallet, so the pallet does not move. This system is recommended for loads that are either very heavy, or for light, unstable, or irregular loads.

Wrapper Function Levels:

Manually Operated

Fully operator controlled. Operator attaches the film to the load, manually controls the release of the film and the up & down movement of the film carriage. Good for low volume use.

Semi-Automatic

Requires an operator to attach the film to the pallet load, then a single button wraps the pallet automatically to a programmable pattern of number of wraps and extra top or bottom wraps.

Fully Automatic

Requires no operator control. Attaches film to the load, wraps load and cuts film automatically. Operator transfers the loads on and off the table or pallets can feed automatically into the wrapper from a conveyor system.

Common Wrapper Options:

Pre-Stretch Film Carriage: Pre-stretches film from 50% to 300% before it is applied to load. Achieves a tighter wrap using less film. Film savings are significant compared to manual wrapping and offers a quick return on investment.

Ramp: Used to load product onto a low profile machine with a hand pallet jack truck or electric jack.

Ramp Extension: Required with longer electric power jacks and jacks with extended fork lengths.

Scale Package: Scale integrated into the stretch wrapper turntable for simultaneous wrap & weigh operation.

Dual Turntable: Two turntables share a common tower and film carriage. This allows wrapping of one load while the operator is unloading/loading product on the other turntable. Increases efficiency for high volume operations.

Auto Film Cutter: Cuts the film automatically after your load has finished wrapping, saving operator time.

Top Platen: Hold cartons or other irregular products together, from above the load, while the pallet is rotating.

We recommend that you consult a packaging equipment specialist to determine the proper machine for your specific application and to provide a cost justification proposal for the equipment.

We Provide Free Assistance for All Your Packaging Requirements!